

Part 1. Report Cover

Report Number: DLA005

Report Date: 7 Sep 02

Title: Performance Oriented Packaging Testing of a PPP-B-601, Style A, Cleated-Plywood Box With Skids, 38" by 38" by 38" (ID), Containing Packaged Solids- Packing Groups I, II, and III (All Surface Modes)

Responsible Individual: Francis S. Flynn

Performing Activity: LOGSA Packaging, Storage,
and Containerization Center
ATTN: AMXLS-AT
11 Hap Arnold Boulevard
Tobyhanna, PA 18466-5097

Performing Activity's Reference(s): TT 10-02; 9HTRR; TE 35-97;
AMC 13-88

Report Type: Interim Final

DTIC Distribution: N/A

Requesting Organization:

Defense Logistics Agency
Defense Distribution Center
ATTN DDC J-3/J-4-0
2001 Mission Drive
New Cumberland PA 17070-5000

Requesting Organization's Reference(s):

DLA Memo, 12 Dec 01

Test Results: ___ single X combination ___ composite

Section I. Pre-test Conditions

For initial testing, one box was received in new condition, from the DDSF post box fabrication shop.

The following identification schema designates the packaging specimen used for the test(s) indicated.

<u>Specimen No.</u>	<u>Test</u>
A	stack test
A	repetitive-shock vibration test
A	flat onto bottom, drop test
	flat onto long side, drop test
	flat onto top, drop test
	flat onto short side, drop test
	bottom corner, drop test

Section II. Summary

A. Drop test - 1.8 m		PASS
flat onto the top (face 1)	PASS	
flat onto the bottom (face 3)	PASS	
flat onto long side (face 4)	PASS	
flat onto short side (face 6)	PASS	
bottom corner (5-2-3)	PASS	
B. Leakproofness test -		
restrained under water/soap over seams		N/A
C. Internal pressure test/Hydrostatic pressure test (liq.) -		N/A
D. Stacking test - static load, 2,000 lb, 24 hr		PASS
E. Vibration standard - repetitive-shock, rotary motion		
3.60 Hz., 1 hr		PASS
F. Water resistance test (fiberboard box) -		N/A
G. Compatibility test (liq. in plastics) -		N/A

Test Results (continued)

Section III. Discussion

A. Drop test: 49 CFR §178.603

Test date(s): 8/13/02

- ☐ cold conditioned (0° F, 72 hr)
☒ ambient conditions (~72° F)
☐ standard conditions (50% RH & 23° C)

No.	Ht.	Orientation	Results
A	1.8 m	Flat onto box bottom (3)	Pass/No leaks/rupture; entire contents retained
A	1.8 m	Flat onto box long side (4)	Pass/No leaks/rupture; entire contents retained
A	1.8 m	Flat onto box top (1)	Pass/No leaks/rupture; entire contents retained
A	1.8 m	Flat onto box short side (6)	Pass/No leaks/rupture; entire contents retained
A	1.8 m	Diagonally onto bottom joint corner (5-2-3)	Pass/No leaks/rupture; minor crushing of the 5-2-3 corner; contents retained completely within the box

For each orientation for the drop test, a quick release hook fixed to an overhead crane was used to lift the container for each 1.8 m drop. The impact surface was a steel plate.

In conducting the drop test, all five drops (flat bottom, flat long side, flat top, flat short side, and bottom corner) were performed on the same configuration. The decision to use the same container (configuration) for all five drop orientations was based on the relatively minimal damage demonstrated during previous testing of plywood boxes with different inner containers or articles. Five drops per configuration exceeds 49 CFR §178.603 requirements, as well as both UN and ASTM recommendations (i.e., one drop on a side or corner per box). The use of one configuration for multiple tests and drops is DOD policy as stated in DLAD 4145.41/AR 700-143/AFJI 24-201/NAVSUPINST 4030.55A/MCO 4030.40A, Packaging of Hazardous Material. Also per this policy, any failed orientation(s) can be repeated using another configuration.

B. Leakproofness test: 49 CFR §178.604

N/A. The leakproofness test was not conducted on the box, because the packaging is not intended for the containment of liquids.

C. Internal Pressure/Hydrostatic Pressure test: 49 CFR §178.605

N/A. Testing for the maintenance of internal pressure is not required for this configuration. See note on page C2.

D. Stacking test: See 49 CFR §178.606. **Test date(s):** 5/09/02
 ___ standard conditions (23° C & 50% RH)
X ambient conditions (~72° F)
 ___ high temperature conditions (104° F)

No.	Length	Type	Load/Force	Peak Force	Results	Stability Maintained?
A	24 hr	Static	2,000 lb	N/A lbf	Pass	Yes

A static top load (2,000 lbs) was used for the stack test, because it could hold the load constant for the required 24-hour timeframe. The total top load applied on the empty box was greater than the minimum required for one box based on the outside box height and the gross packaged weight. The top load was to simulate a stack of identical packagings that might be stacked on the packaging during transport.

E. Vibration test: See 49 CFR §178.608. **Test date(s):** 8/12/02

No.	Frequency	Duration	Results
A	3.60 Hz	1 hr	Pass. No leakage, rupture, or damage

To be in compliance with U.S. Department of Transportation standards for packagings bearing the United States mark (USA) as a component of packaging certification marking (49 CFR §173.24a(a)(5)), the vibration test was performed, as a means to determine capability. The test was conducted as prescribed by ASTM D 999, method A2 (Repetitive Shock Test (Rotary Motion)). The test was run for 1 hour, using the plywood box packaging. The packaging was tested using a 4,000-lb vibration table (rotary motion) that had a 1-inch vertical double amplitude (peak-to-peak displacement) such that the packaging was raised from the platform to such a degree that a piece of steel strapping (1.6 mm) could be passed between the bottom of the package and the platform.

F. Water resistance (Cobb Method) test (fiberboard): N/A

G. Compatibility test (plastics packagings only): N/A.

The following personnel performed the aforementioned testing, or had a role in the testing, evaluation, and/or documentation, as reported herein-- Richard D. LaFave, Bruce W. Samson, Timothy L. Reimann, and Karen K. Kimsey

References

- A. Title 49 Code of Federal Regulations, Parts 106-180,** Fall 2002, current as of 10 Jul 02
- B. International Air Transport Association Dangerous Goods Regulations,** 40th edition, 1 January 1999
- C. ASTM D 4919,** Specification for Testing of Hazardous Materials Packagings.
- D. ASTM D 999,** Standard Method for Vibration Testing of Shipping Containers.
- E. ASTM D 951,** Standard Test Method Water Resistance of Shipping Containers by Spray Method.
- F. TAPPI Standard: T 441** Water Absorptiveness of Sized (Non-Bibulous) Paper and Paperboard (Cobb Test).
- G. Recommendations on the Transport of Dangerous Goods,** sixth revised edition, United Nations, New York, 1990.
- H. DLAD 4145.41/AR 700-143/AFJI 24-201/NAVSUPINST 4030.55A/MCO 4030.40A,** Packaging of Hazardous Material, 23 Jul 96
- I. AFJMAN 24-204/TM 38-250/NAVSUP PUB 505/MCO P4030.19G/DLAI4145.3,** Preparing Hazardous Materials for Military Air Shipments, 1 Mar 97

Equipment

Item	Manufacturer	Serial No.	Calibration Expiration Date
4,000-lb vibration table	Gaynes Engr. Co. Franklin Park, IL	G20765	see note
30,000-lb compression tester	Gaynes Engr. Co. Franklin Park, IL	G20950	4/03
release hook	Gaynes Engr. Co. Franklin Park, IL	18211-1	N/R

Note. Equipment is calibrated in accordance with International Safe Transit Association test equipment verification requirements.

Test Applicability

Pass/fail conclusions were based on the particular box specimens, test loads, and the limited quantities submitted for test. Extrapolation to other materials, other manufacturers, other applications, different inner packagings, container sizes, or lesser inner quantities is the responsibility of the packaging design agency or applicable higher headquarters. Extrapolation of test results based on less than the minimum recommended number of test specimens is also the responsibility of the packaging design agency or applicable higher headquarters.

Testing was performed per *Title 49 Code of Federal Regulations*.

Performance testing was undertaken and completed at the request of an agency responsible for shipment of the dangerous good(s). The completion of successful required performance tests does not, by itself, authorize the marking and transportation of the dangerous good(s). Applicable modal regulations should be consulted concerning the relationship of performance testing completed and the dangerous good(s).

The required performance tests are intended to evaluate the performance of the packaging components. The criteria used to evaluate packaging performance is whether the contents of the packaging are retained within the outer packaging, should damage to the outer packaging occur, and secondly, if any inner packaging of hazardous materials leaks, ruptures, or is damaged so as to affect transportation safety. The successful completion of the required tests do not ensure the undamaged delivery or survivability of the actual commodity/item. Separate testing is necessary to assure the stability of any explosive item.

Before a configuration can be certified by the person(s) authorizing shipment, the appropriate packaging for the particular hazardous materials and mode of transportation must be determined, and the item(s) must be prepared for shipment per applicable regulations. The chosen configuration must have been performance tested in accordance with the size, the shape, and the weight constraints posed by the configuration to be certified. The testing reported herein should not be construed as blanket certification of any configuration that simply uses the performance tested outer box. Packaging paragraphs apply.

A-1

RN: DLA005

Appendix B

Test Data Sheet

Section I. Test Product

Physical State: X solid liquid gas aerosol

Test Product(s) Used: Thirteen boxes, 16½" x 8" x 8", containing solids 132 lbs. (10.15 lbs. ea); nine boxes, 9½" x 8" x 6½", containing solids 109 lbs. (12.11 lbs. ea); four BA-358U batteries, 9" x 6½" x 4¾", 40 lbs. (10 lbs. ea); five, BA-358U batteries, single, 8¾" x 2¾" x 2¾", 24 lbs. (4.81 lbs. ea); and two, BA-270-2 batteries, 7¾" x 2¾" x 2½", 5 lbs. (2.5 lbs. ea).

Amount Per Container:

Item Weight-- 310 lbs.
Tare Weight-- 140 lbs.
Gross Weight-- 450 lbs.

Section II. Test Parameters

Drop Height: Ref: 49 CFR §178.603

 X 1.8 m; 71 in. (PG I, II, & III, SG ≤1.2 or solids)
 1.2 m; 47 in. (PG II & III, SG ≤1.2 or solids)
 0.8 m; 32 in. (PG III, SG ≤1.2 or solids)
 from-- PG I: SG x 1.5 m x 39.37 in.
 PG II: SG x 1.0 m x 39.37 in.
 PG III: SG x 0.67 m x 26.38 in.

Stacking Weight Formula Solids

Variables	Inputs		
h height, drum/box	43		
n # stacked containers	XXXXXX	2.74	
w gross packaging weight	450		
A Stacking weight	XXXXXX	783	784

NOTE: A=(n-1)*w

A=applied load in pounds

n=(118/h), minimum number of containers that when stacked, reach a height of 3m

w=maximum weight of one packed container in pounds

Appendix C

Packaging Data Sheet

Section I. Exterior Shipping Container

Packaging Category: ____ single X combination ____ composite

UN Type: Plywood boxes (49 CFR §178.514) UN Code: 4D

Specification No.: PPP-B-601; Style A; Cleated plywood box with
skids; 140 lbs.; 38" x 38" x 38" (ID); 40½" x 40½" x 40½" (OD)

Manufacturer: Department of Defense, Defense Distribution Region East
Susquehanna, West Container Fabrication Branch, Mechanicsburg, PA
17055

Date(s) of Manufacture: February 2002

Closure Method: The outer plywood box was sealed using 8 penny cement
coated sinkers. The box was then banded with ¾" x .023" flat steel
strapping; 3 lengthwise and 3 girthwise. (See drawing)

Static Electricity Protection: N/A


Polyethylene Bag Manufacturer: Rutan Polyethylene, MAHWAH, NJ (4 MIL)
Size: 48" x 40" x 85"

1" wide, pressure sensitive tape, filament, IAW
ASTM D5330, Type II; NSN-- 7510-00-582-4772

Appendix C (Continued)**Section II. Interior Packaging**

Quantity of Inner Containers: Thirteen boxes, 16½" x 8" x 8", containing solids 132 lbs. (10.15 lbs. ea); nine boxes, 9½" x 8" x 6½", containing solids 109 lbs. (12.11 lbs. ea); four BA-358U batteries, 9" x 6½" x 4¾", 40 lbs. (10 lbs. ea); five, BA-358U batteries, single, 8¾" x 2¾" x 2¾", 24 lbs. (4.81 lbs. ea); and two, BA-270-2 batteries, 7¾" x 2¾" x 2½", 5 lbs. (2.5 lbs. ea). See D-2 Photo.

Appendix D
Drawing



ITEM	DESCRIPTION
1	PPP-B-601, STYLE A, CLEATED-PLYWOOD BOX WITH TWO SKIDS AND INTERMEDIATE CLEATS 38 x 38 x 38 IN. (ID)
2	4 MIL POLYETHYLENE LINER, FOLDED & SEALED WITH 1" FIBER-REINFORCED TAPE, NSN 7510-00-582-4772
3	¾ x .023 IN. STEEL STRAPPING, FLAT, TYPE 1 REGULAR DUTY, FINISH A, IAW ASTM D 3953, 3 GIRTHWISE, 3 LENGTHWISE BANDS

Appendix D (Continued)



Appendix D (Continued)

